











SHUMFITT Shenzhen Shumatt Technology Co., Ltd

SPRING

0445120296 Injector CRIN2-16 Technical File

States States Street	<u>8</u>
1.0445120296 Injector's Introduction	2
11 0445120296 Injector's Basic Information	2
1.2. 0445120296 Injector's Common Part Number	2
1 3 0445120296 Injector's Matching Information	2
1.4.0445120296 Injector's Parameter	2
1.5.0445120296 Injector's Specifications and Dimensions	2
	3
1.6. 0445120296 Injector's Quality Control 1.7. 0445120296 Injector's Customized Service	3
1.8.0445120296 Injector's Packing List and Package Size	5
1 10 0445120296 Injector's Warranty Instructions	
1.11.0445120296 Injector's Manufacturer 2.0445120296 Injector Technical Support	6
2.0445120296 Injector Technical Support	6
2 1 0445120296 Injector's Part Number Location	6
2.2.0445120296 Injector's Application Scenarios	7
2.3.0445120296 Injector's Installation	7
2.4. 0445120296 Injector 's Reasons for Not Working Normally	8
2.4. 0445120296 Injector 's Reasons for Not Working Normally 2.5. 0445120296 Injector 's Causes of Damage	8
2.6.0445120296 Injector's Technical Support Obtaining Methods	9
2.6.0445120296 Injector's Technical Support Obtaining Methods	9
3 1 0445120296 Injector's Purchase Payment Term	g
3.2.0445120296 Injector's Main Sales Markets 3.3.0445120296 Injector's Declaration Requirements	9
3.3.0445120296 Injector's Declaration Requirements	9
3.4.0445120296 Injector's Shipping Ways	9
3.4.0445120296 Injector's Shipping Ways 3.5.0445120296 Injector's Lead time1	0
3.6.0445120296 Injector's Logistics Time for Destination Out of China's Areas	10
3.7.0445120296 Injector's Packing	0
4.0445120296 Injector's Storage Standard1	
	2
5. Company Information	2
5.2. Sales-men's Contact Information	.3
. 20. 20. 20. 20. 20. 20. 20. 20. 20. 20	Ç.
SHARAL SHERT S	je.
SANDALL S	je je

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

The The The Tree The

. mpr

Tel: +8675523215133 Website : www.shumatt.com

and a strength and the strength and the

. and

0445120296 Injector CRIN2-16 Technical File

SALER

SARA

1.0445120296 Injector's Introduction

stron. stron. stron. stron. stron. stron 1.1. 0445120296 Injector's Basic Information

	ijeetor 5 Busie miterination	
Title	China made new high quality diesel injector 0445120296 fuel injector CRIN2-16	ç
SKU 1 9	DGH130445120296	-98
SKU 2	/	
1.2. 0445120296	njector's Common Part Number	şê

1.2. 0445120296 Injector's Common Part Number

(1) Injector's Exchange Information

(=,,)================================		<u>ah ah ah ah</u>
Injector Part Number	Universal Part Number	Re-manufactured Part Number
		11 - 241 - 241 - 241
0445120296	Dr. Dr. Dr. Dr.	the the the the
and and and and an	States States States States 2	and the state state of the

(2) Injector's Application Information

Injector Part Number	Car Number	Car number	Car Number
910 ⁰⁰¹⁵ 910 ⁰⁰¹⁵ 0445120296		REPORT SHERT SHERT SHERT SH	anti shanti sh
States States	Mannin SHAR NI SHARN SHARNING	ALTERT SHARET SHARET SHARET SH	CONT SHERRY SHE

(3) Injector's Part Number Common Writing

STATIST SHATSAT 0445120296, 0 445 120 296, 0445 120 296, 0445120 296, 0 445120296, 0 445120 296

1.3.0445120296 Injector's Matching Information

								107 - A 107 -			
Vehicle Brand	Series	Car Model	Engine Model	Production Date	Power (KW)	Hourse Power	Emission Standards	Manufacturer	Emissions (L)	Cylinder	Power Source (V)
	$\mathcal{P}^{\mu} = \mathcal{P}^{\mu}$	and the second	all the second	a 1997 - a 1	8°'	er .	Sec. 1	an an	. 1. 18 March	1. 19 March 1.	. 2

STRATEST?

STRATT

1.4.0445120296 Injector's Parameter

SPECTRE Adaptation System: Common Rail System **Injector Series:** 120 Series

Parameter Performance: CRIN2-16

P PROTO all the P.F.F. Matching Accessories: Gasket F 00R J02 175 (7.73*14.36*1.49)

Injector Type: Electromagnetic Injector

Support System Maximum Pressure: 1,600 Vehicle Configuration Information: /

. Then Then Then Then Then Then SPARAT 1.5.0445120296 Injector's Specifications and Dimensions ast.

Injector Size: 21.5cm*4 cm *4 cm = 344cm³ (L*W*H=V)

and the addition of the additi

Mob/WhatsApp: +86 13410541523 Email : ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

Injector_Net Weight: 0.55kg Gross Weight: 0.6kg Injector Quality: China Made Brand New Package Size: 28cm*7 cm *7 cm = 1372 cm³ Injector Type: Diesel Common Rail Injector

MOQ: 4 Pieces

1.6. 0445120296 Injector's Quality Control

(1) Injector Testing

-1. P

1920 All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque,

(3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop. stër

1.7. 0445120296 Injector's Customized Service

(1) Injector's Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.

Contractor of			an in in in its constant in it
and and and a	Injector house lettering	Injector solenoid valve	on an an a
Injector nozzle engraving	and QR code	engraving	Injector box and label

(2) Injector's Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

A Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems.

1.8.0445120296 Injector's Packing List and Package Size

Mob/WhatsApp: +86 13410541523 Email:ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

(1) Injector	Spare Parts List		
No.		2.00	
Ster Ste	Դուծորելու, Դութերիս, Դութերիս, Դութերիս,	Str. Str. Str.	91
Strittinge Statist			st ^{er} O st ^e
Name	Fuel Injector	O-Ring	Gasket F 00R J02 175
St. 200		Ensure to meet the	Made of brass, used to ensure the
Description	Fuel injector part number: 0445120296	standard of the sealing	tight fit between the injector cap end
	. The The The The	performance between the injector and the engine	and the engine
No.	4	5	6 3 6 3 S
Strillmage Strill			salah isti
Name	Nozzle Protective Cover Cap	Injector House Protective Cover Cap	Solenoid Valve Protective Cap
Description	Protect nozzle holes from being polluted and blocked	Protect oil inlet from being polluted and blocked	Protect the solenoid valve body and terminals from being damaged by external forces
No		8,000	
an Image and			
Name	VCI Anti-rust Bag	Bubble Bag	Injector Packing Box
Description	Prevent fuel injector from rusting	Prevent the injector from being damaged by external forces	Place injector and injector accessories
		· · · ·	

▲ Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

 O-ring and gasket are disposable installation accessories, and need to be replaced for re-installation.


▲ The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused.

VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.

▲ The injector and the installation parts should be coated with appropriate sealing oil during installation.

(2) Injector Box Size

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com $\phi \phi^{(i)}$



1.9.0445120296 Injector's Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.

- Sec.	100	an Bar	- SHATHET SHATHET SHATHET SHATHET SHATHET SHATHET SHATHET SHATHET
BOTEN	测试报告	4.05.2019 10:42:09	- Stand, Strand, Strand, Strand, Strand, Strand, Strand, Strand,
苏伸 <u>企业</u> :	激は:		
АД:			- SHARAT SHARAT SHARAT SHARAT SHARAT SHARAT SHARAT SHARAT
(*)創設: (表:	送检单位:		- Stread, Stread, Stread, Stread, Stread, Stread, Stread,
a:	客户姓名:		
萨拟述:			- SHADAL SHADAL SHADAL SHADAL SHADAL SHADAL SHADAL SHADAL SHADAL
사名标: 數字 등·零件등:	<u>x</u>		States, strates, strates, strates, strates, strates, strates, states,
¥A:			
52 18 070 - C05000-6511	检测结果		STRUMET STRUMET STRUMET STRUMET STRUMET STRUMET STRUMET STRUMET
略和GGR的 LEAK TEST: 32	999628 K52K063	30.8±'+4 🗸	Strange, Strange, Strange, Strange, Strange, Strange, Strange, Strange,
Radi: at WRRAL at Maa: 2015	+ 353 1473±185 C3 2185±144 C3		
TL: 284 UC: 141	346±85 60 160±48 60	······ ··· ·· ·· ·· ·· ·· ·· ·· ·· ·· ·	SHEADERT SHEADERT SHEADERT SHEADERT SHEADERT SHEADERT SHEADERT
WE: 4,7	41:13 ()	• V	24 The second strates, 24 Tour 24 Tour 24 Tour 24 Tour 24 Tour
			- SHARANT SHARANT SHARANT SHARANT SHARANT SHARANT SHARANT
1 []a2]a3 []a4]a5 推修前	6d1d338899845		- 21 ^{2,000,}
arti.	. 615 - 10	ant and	

1.10.0445120296 Injector's Warranty Instructions

(1) . Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) . Injector Warranty Coverage

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133 Website : www.shumatt.com

Think Then The Arts of the Arts of the Arts

Within 15 days after customer receives the 0445120296 injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the 0445120296 injector has performance problems during the warranty period (3 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 - 91⁸² months from the date of repairing.

(3) . Injector Out of Warranty Coverage

The warranty period has expired.

- 51^{0,008} 51930 Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, wart'i earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set A.S. C. STATES STATES STATES STATES -34⁵⁰⁷⁰ All Carrier at the at the fire).

Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and a part a part a part of parts of the state and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine SPREAM " and the address of the address of the maintenance manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine ATTRACT maintenance manual.

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine 51 maintenance manual. di la

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual. AND SARAT SARAT SPR. ED. T

STREAM P

1.11.0445120296 Injector's Manufacturer

Injector's manufacturer: Shenzhen Shumatt Technology Co., Ltd

2.0445120296 Injector Technical Support


2.1.0445120296 Injector's Part Number Location

Mob/WhatsApp: +86 13410541523 Email:ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

Si No. Name brand, logo, part number,
brand, logo, part number.
series number
B nozzle part number
В
A Standard and and and and and

2.2.0445120296 Injector's Application Scenarios

Common rail system is an oil supply method refers to the diesel oil from the fuel tank sucked out by the gear pump through the oil-water separator and the gear pump to diesel fine filter, high-pressure pump, common rail pipe, and fuel injector, all together with the closed-loop fuel supply system composed of sensors and ECU that completely separates the generation of injection pressure and the injection process from each other.



- 30.1	- 34" - 34"	- 347	- 94° - 94° -	ie noi i	<u>- 341'' - 341'' - 341</u>	- 34	<u>r 34, 34</u> ,
No.	Name	No.	Name	No.	Name	No.	Name
S. D. S. C.	Tank and	5,80	Common Rail Pressure Sensor	9	Engine Crankshaft Sensor	A	High Pressure Oil Circuit
2	Diesel Filter	6	Common Rail Pipe	10	Camshaft Sensor	B	Low Pressure Oil Circuit
\$\ 3 \000	High-Pressure Pump	7. ³³	Injector	S.11	ECU Electronic Control Unit	19 - C	an at an at
4	Fuel Gear Pump	8	Accelerator Pedal				
. 50	ti atti a	18 ⁵⁶ - 18	the state state		Star Same	all the	ant and a

2.3.0445120296 Injector's Installation

(1) .0445120296 Injector's Installation Precautions:

▲ The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual,

▲ Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

▲ When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

spots, etc.

Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the fuel injector.

When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket $-gl^{3/2}$ - 3^{8,0} and O-ring.

A Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

A When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are not deformed, and install it in strict accordance with the operation steps of the engine maintenance

▲ It is forbidden to operate the bare injector for a long time in an environment with serious dust A TRACK NUTRE C pollution and corrosion to iron products.

SAIDETT

It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

2.4. 0445120296 Injector 's Reasons for Not Working Normally

(1) There is air in the oil circuit of the engine fuel system.

(2) Vehicle oil pump oil supply system is not normal.

(3) Engine common rail system oil leakage or pressure limiting valve damage.

(4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel SARAT injector of the vehicle.

at the

(5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked. and the - ¹⁷ - 300 19 C

Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged so as to prevent the fuel injector from not working properly after being replaced. SPANDAT? SPACE ATTE AND AND AND AND AND AND

2.5. 0445120296 Injector 's Causes of Damage

(1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the injector .

(2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.

(3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector. 100 19 an 100 100 d Da 8 S -

(4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.

(5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.

(6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel

injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.

(7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector.

(8) The injector will be damaged naturally at the end of its working life.

(9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.

A Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

2.6.0445120296 Injector's Technical Support Obtaining Methods

(1) Injector Technical File, visit <u>http://shumatt.com</u> to get the technical file.

Star.

(2) Injector Technical Videos

1,500

Facebook: Visit https://www.facebook.com/hison.li to get the technical videos, constantly follow can get STREET, T THURSON . REPART 237877 AURIE I PORES more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV_mAfxh_Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit http://shumatt.com to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit http://shumatt.com to get the download and installation tutorial

(4) Search The fuel injector test data through TruckBook Parts EPC APP. $S^{0,0}$

3.0445120296 Injector's Purchase and Delivery

3.1.0445120296 Injector's Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat Please **c**ontact our salesmen for specific payment information.

3.2.0445120296 Injector's Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

1885 C 1995 all's and the 18 May 19 3.3.0445120296 Injector's Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4.0445120296 Injector's Shipping Ways

120 e^{2N} Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

100

Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

Tel: +8675523215133 Website : www.shumatt.com

1⁹20

17.00

1 No

3.5.0445120296 Injector's Lead time

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and special cases).

51925057

 $\wp^{[0]}$

and which which which which which when -50 3.6.0445120296 Injector's Logistics Time for Destination Out of China's Areas 100

DHL Logistics Time :

Country or Region of Departure		Hong Ko China	0,	Australia and Zealand	Furono Amorica		America	Other Countries	ş
China's Mainlar	nd	7 Day	s 7 Days	8 Days	S.	8 Days	8-12 Days	7-10 Days	ç
UPS Logistics T	ime:	Counti	y or Region of Departu	re: China's M	lainlan	d	1.0°	Streen .	4
Country of Destination		mated al Time	Country of Destination	Estimated Arrival Time	Cou	intry of Desti	nation	Estimated Arrival Time	
Shullapan Shull	3	Days	UK A	5-7Days	st.	Egypt	r de	5-7 Days	ų,
Turkey	5-7	Days	Singapore	3 Days		Switzerland	t -	5-7 Days	
Bahrain	5-7	Days	antatvia	7-10 Days	- 19 - Ali	New Zealan	d ²² 2	7-10 Days	1
Sri Lanka	Sri Lanka 5-7		Thailand	3 Days	20	Austria		5-7 Days	1
Romania	्रिं 5 -7	Days	Vietnam	3-5 Days	б ¹ .,	Estonia		5-7 Days	2
Malaysia	3-5	Days	Israel	5-7 Days	- 37	Mexico	37	7-10 Days	1
France	5 -7	Days	America	5-7 Days	_e ⊰ Un	ited Arab Em	irates	5-7 Days	ç
Staly Stale	5-7	Days	Netherlands	5-7 Days	310	Bengal	37	7-10 Days	\$
Lebanon	5-7	Days	Philippine	3-5 Days		Greece	~	7-10 Days	c
South Korea	3	Days	Spain	5-7 Days	Myanmar		an and	5-7 Days	-
Canada	5-7	Days	Germany	5-7 Days		Saudi Arabia		7-10 Days	
Portugal	5-7	Days	Australia	5-7 Days	17. 18	South Afric	9 ⁵⁰	7-10 Days	1
Denmark	5-7	Days	Belgium	5-7 Days	39.1	Ukraine	200	7-10 Days	
India	7-10) Days	Qatar	7-10 Days	St.	Poland	ant a	5-7 Days	ç
Indonesia	3-5	Days	Morocco	7-10 Days	- Sty	Pakistan	24	7-10 Days	ş
Kuwait	7-10) Days	a a a		<u>.</u>				ç

The logistics time is for reference only subjects are according to the actual arrival.

3.7.0445120296 Injector's Packing

and the april 1 Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2. International express packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3. 2.10 2.10


Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4, $\omega^{[0]}$ also, the products can be packaged according to customers' requirements.

The packing tray is made of plastic and can be recycled.

Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury. - 5874

Mob/WhatsApp: +86 13410541523 Email : ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd



2.5755 Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties All all all

4.0445120296 Injector's Storage Standard

(1) Choose a suitable storage place

17 N 1920 The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry. SALJER SP STOR

(2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

Mob/WhatsApp: +86 13410541523 Email:ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133 Website : www.shumatt.com -98° -

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

- **A** It is forbidden to leave the injector exposed in the air for a long time.
 - It is forbidden to store acids, alkalis, salts and other substances together with the injector.
 - The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information



Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

100

After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: <u>1.10.0445120296 Injector Warranty Instructions</u>)

- 200

and the

1.00

- 15

No.	Name	WeChat/WhatsApp	Email	Facebook	YouTube
1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li
2	1vy	+86-18025299821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY
3 ,000	Rebecca	+86-18025349821	sales01@shumatt.com	SHUMATT	SHUMATT Rebecca
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie
7	Ada	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li
9 . 🖽	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca
10	ST Eric	+86 18319033618	sales3@shumatt.com	Ster Stor	98° - 98°
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt
12, 🕬	Sylvia	+86 18312499884	sales6@shumatt.com	. I	1
31	200 SU 2	Visit http://shumatt.com to o	btain the latest information of salesme	en String String	80° - 80°
		PS: Shumatt's sales-men's	emails are all end with @shumatt.com		

SPREAMENT

519.39505

5.2. Sales-men's Contact Information

6. Copyright Statement

 $\mathbb{S}^{\mathbb{N}^{N}}$

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "0445120296 Injector CRIN2-16 Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "0445120296 Injector CRIN2-16 Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "0445120296 Injector CRIN2-16 Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "0445120296 Injector CRIN2-16 Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.

States.

SPATTOR

5812595

519375

3A-578

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd