**C7** Injector **383-9427** Technical File SKU: G1DS15003839427





STRUMENT

SPUTT

States .

SPARST

C7 Injector 383-9427 Technical File 39.50

SPREAT

SPACE

SPRINT

SHLOWIT

 $\mathcal{D}_{\mathcal{C}}^{(0)}$ 

SPREEDET

 $\otimes^{\mathbb{R}^{1}}$ 

 $\otimes^{[0]}$ 

## an stant stant

1. 383-9427 Injector Introduction
1.1. 383-9427 Injector Basic Information
1.2. 383-9427 Injector Common Part Number1
1.3. 383-9427 Injector Part Number Common Writing1
1.4. 383-9427 Injector Parameter1
1.5. 383-9427 Injector Specifications and Dimensions1
1.6. 383-9427 Injector Quality Control 1
1.7. 383-9427 Injector Customized Service2
1.8. 383-9427 Injector Packing List and Package Size
1.9. 383-9427 Injector Testing Standard and Certificate
1,10. 383-9427 Injector Warranty Instructions
1.10. 383-9427 Injector Warranty Instructions
2. 383-9427 Injector Technical Support
2.1. 383-9427 Injector Part Number Location5
2.2. 326-4700 Injector Application Scenarios
2.3. 383-9427 Injector Installation
2.4. 383-9427 Injector Reasons of Not Working Normally7
2.5. 383-9427 Injector Causes to Damage7
2.6. 383-9427 Injector Technical Support Obtaining Methods
3. 383-9427 Injector Purchase and Delivery
3.1.383-9427 Injector Purchase Payment Term83.2. 383-9427 Injector Main Sales Markets8
3.2. 383-9427 Injector Main Sales Markets8
3.3. 383-9427 Injector Declaration Requirements8
3.4. 383-9427 Injector Shipping Ways
3.5. 326-4700 Injector Lead time
3.6.383-9427 Injector Logistics Time for Destination Out of China's Areas
3.7. 383-9427 Injector Packing
4. 383-9427 Injector Storage Standard
5. Company Information
5.1. Company Introduction11
5.2. Contact Information
6. Copyright Statement
and a start at and at

ATT STRAFT STRAFT STRAFT STRAFT STRAFT STRAFT STRAFT STRAFT STR

### C7 Injector 383-9427 Technical File

#### 1. 383-9427 Injector Introduction

1.1.383-9427 Injec	tor Basi	c Inform	ation	States - States -	NAME AND	ALTER .	and and a	A. C. C.
Title	0	Chin	a made	new injector 383-9	9427 fuel injec	tor for C7	Engine	
SKU 1				G1DS150	03839427		de.	

#### 1.2. 383-9427 Injector Common Part Number

#### (1) Injector Exchange Information

Injector Part Number	Re-manufactured Part Number	Replacement Number	OE Number
383-9427	The Tol The	The The The	The Man The
3839427	19 <sup>10</sup> - 19 <sup>10</sup> - 19 <sup>10</sup> - 19	the star star st	an lan ta

#### (2) 383-9427 Matching Information

Car Mod	del	Ca	r Model		Car	Model		Car Mod	el	Car	Model
- Si - Si		u 16.			14 Y	a da		- Yei - Yei		61 - F	
C7			/			/		/			/
- 1 C	1	100	100	100	100	100		1	100		100
1023	1000	1000	1000	1000	1000	1990	1000	1000	1000	1000	

#### 1.3. 383-9427 Injector Part Number Common Writing

#### 383-9427, 383 9427, 3839427

#### 1.4. 383-9427 Injector Parameter

Adaptation System: HEUI System

Injector Series: C7 Series

#### Injector Type: Electromagnetic Injector

Vehicle Configuration Information:C7 Engines

### 1.5. 383-9427 Injector Specifications and Dimensions

**Injector Size:** 35cm\* 14cm \*14cm =6860cm<sup>3</sup> (L\*W\*H=V) Injector Net Weight: 1.9kg

 $c \delta^{2,2}$ 

Injector Gross Weight: 2kg

Injector Quality: China Made New

Package Size: 38cm\* 15cm \*15cm = 8550cm<sup>3</sup>

Injector Type: Diesel Common Rail Injector MOQ: 4 Pieces

#### 1.6. 383-9427 Injector Quality Control

#### (1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

#### (2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque.

#### (3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a

Mob/Whatsapp: +86 13410541523 Email :ruby@shumatt.com © 2023 Shenzhen Shumatt Technology Co., Ltd

total of no less than three times for factory inspection, and the fuel injector installation testing environment =10,0001T SPERMIT SAUDAT are progressed in dust-free workshop.

#### 1.7. 383-9427 Injector Customized Service

(1) Injector Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



#### (2) Injector Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark REPRESE ALERT' authorization and the sample of logo image file.

A Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems. S. STORY . 15

# 1.8. 383-9427 Injector Packing List and Package Size

(1) Injector Spare Parts List

(17) h		- 45 - 45 - 45 - 45 -	<u> </u>
No.	1	2	3
Image	art and		Curroston pro
Name	Fuel Injector	O-Ring	Nozzle Protective Cover Cap
Description	Fuel injector part number 383-9427	Ensure to meet the standard of the sealing performance between the injector and the engine	Protect nozzle holes from being polluted and blocked
No.	4	5	6
image anti-			
Name	VCI Anti-rust Bag	Injector Packing Box	Nozzle Gasket
Description	Prevent fuel injector from rusting	Package for injector and injector accessories	Used to ensure the tight fit between the tight cap end of the injector and the engine
ANTIN' ANTI	N. Strand Strand Strand St.	States - Street, Street, Street,	ALTER ALTER ALTER -

A Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury. 

Mob/Whatsapp: +86 13410541523 Email :ruby@shumatt.com © 2023 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com

2/14

## **SHUMFITT** Shenzhen Shumatt Technology Co., Ltd

A O-ring and gasket are disposable installation accessories, and need to be replaced for SPARE - SRIM 3215 re-installation. A The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused. S.C. 15 12 18 17 C cC -A VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly 177682.8 A TRACK after using. ALTERN'S A.M.ST. STATISTICS STATISTICS A The injector and the installation parts should be coated with appropriate sealing oil during

installation.

 $g^{(n)}$ SHUTTER . SPR. STR. ST. SHEPPER SPLINET (2) Injector Box Size 3.5<sup>097</sup>



#### 1.9. 383-9427 Injector Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.



Mob/Whatsapp: +86 13410541523 Email :ruby@shumatt.com © 2023 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com



#### 1.10. 383-9427 Injector Warranty Instructions

## (1) Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman. Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

#### (2) Injector Warranty Coverage

Within 15 days after customer receives the 383-9427 injector, if there is a performance failure and the Station . product has no appearance damage, customer can choose to replace it or repair it;

If the 383-9427 injector has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the Str. Str. product is confirmed to be fault-free.

Let Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

#### (3) Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire). Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Mob/Whatsapp: +86 13410541523 Email :ruby@shumatt.com © 2023 Shenzhen Shumatt Technology Co., Ltd  $\omega^{\otimes}$ 

## **SHUMFITT** Shenzhen Shumatt Technology Co., Ltd

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

#### 1.11. 383-9427 Injector Manufacturer

Injector manufacturer: Shenzhen Shumatt Technology Co., Ltd

#### 2. 383-9427 Injector Technical Support

#### 2.1. 383-9427 Injector Part Number Location

1) E.g.: The injector part number see as follows

COURS 11		OUT -		1000 CM CM C		
	51 51	Δ	20. 20.	No.	Name	
st <sup>o</sup>			Start Starts	ST STATE AND STATE	brand, logo, part number, series number	ġŝ
st	B		DATE T SPARTS	ri <b>B</b> ri Stellie Stelli	nozzle part number	d.
- Sta	100 - 3A.S.	and and a second second	SPATIAL SPAT	LL PROPERTY PROPERTY	NT SAUDAT SAUDAT SAUDAT SAUDAT S	gi.


#### 2.2. 326-4700 Injector Application Scenarios

Suitable Car Model: **Caterpillar C7** Engines





Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd



#### 2.3. 383-9427 Injector Installation

(1) 383-9427 Injector Installation Precautions:

The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual;

SHURP

A Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the fuel injector.

A When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket and O-ring.

▲ Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

A When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are

not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual.

CETT. at in 65 15 -18 C 18 C -A It is forbidden to operate the bare injector for a long time in an environment with serious dust

#### pollution and corrosion to iron products.

 $\mathcal{A}^{(2)}$ 32.58 2.9<sup>58</sup> It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

#### 2.4. 383-9427 Injector Reasons of Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump oil supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel
- injector of the vehicle.
- 514,500 SP1208 (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked. State State

蛊 Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged so as to prevent the fuel injector from not working properly after being replaced.

#### 2.5. 383-9427 Injector Causes to Damage

- (1) Don't operate properly according to engine maintenance manual during dis-assembly or installation, resulting in damage to the injector.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the
- water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive
- exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons SALEDR can cause damage to the injector.
- (4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and Start. cause damage to the fuel injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.
- (6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector. 537.505
- (8) The injector will be damaged naturally at the end of its working life.
- 38.<sup>208</sup> (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.  $\mathcal{A}^{\mathbb{Q}^3}$

Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

Mob/Whatsapp: +86 13410541523 Email :ruby@shumatt.com © 2023 Shenzhen Shumatt Technology Co., Ltd

2.6. 383-9427 Injector Technical Support Obtaining Methods

(1) Injector Technical File, visit <u>http://shumatt.com</u> to get the technical file.

(2) Injector Technical VideosFacebook: Visit <u>https://www.facebook.com/hison.li</u> to get the technical videos, constantly follow can get

**Facebook:** Visit <u>https://www.facebook.com/hison.li</u> to get the technical videos, constantly follow can get more information.

**YouTube:** <u>https://www.youtube.com/channel/UCByvYBx7VjV\_mAfxh\_Hu-aw</u> to get the technical videos, constantly follow can get more information.

**Shumatt:** Visit http://shumatt.com to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit <u>http://shumatt.com</u> to get the download and installation tutorial.

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

#### 3. 383-9427 Injector Purchase and Delivery

3.1.383-9427 Injector Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

#### 3.2. 383-9427 Injector Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

#### 3.3. 383-9427 Injector Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

SHIP ST

#### 3.4. 383-9427 Injector Shipping Ways

**Destination in China areas:** SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

**Destinations out of China's areas:** DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

#### 3.5. 326-4700 Injector Lead time

**Lead time:** Send out within 3 – 7 working days after receiving payment (Except for special products and special cases).

3.6.383-9427 Injector Logistics Time for Destination Out of China's Areas

#### DHL Logistics Time:

DITE LOGISTICS							
Country or Regio Departure	on of Hong Kong China	, Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries	$\mathcal{A}_{\mathcal{G}}^{(i)}$
China's Mainla	nd 7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days	
<b>UPS Logistics</b>	Time: Country o	r Region of Departur	e: China's Mainla	and	and and	S. april	
Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of De	stination	Estimated Arrival Time	Bara
Japan	3 Days	UK	5-7Days	Egypt	18 <sup>56</sup> . 18	5-7 Days	Ι.,
Turkey	5-7 Days	Singapore	3 Days	Switzerl	and Street	5-7 Days	ф?°
Bahrain	5-7 Days	Latvia	7-10 Days	New Zea	land	7-10 Days	

Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com

Snenznen Snumatt lechnology Co., Ltd									
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days				
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days				
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days	251 			
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days				
Italy Street	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days	20			
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days				
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days	$\mathcal{P}_{\mathcal{Q}}$			
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days				
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days	de.			
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days				
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days	. 41			
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days	879			
Kuwait	7-10 Days	The The D	The Mar	The The	The Stee				

The logistics time is for reference only, subjects are according to the actual arrival.

#### 3.7. 383-9427 Injector Packing

**Domestic express packaging:** Usually wrapped in waterproof scotch tape, such as picture No.2. **International express packaging:** Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

The The The The

100

 $\phi^{(i)}$ 

**Pallet Shipping:** Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4,also, the products can be packaged according to customers' requirements.

A The packing tray is made of plastic and can be recycled.

Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



**Domestic express packaging:** Wrapped by Transparent tape International express packaging: Wrapped with yellow tape after wrapping black protective film

Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com

9/14



Pic No. 4

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

### -A.S. 4. 383-9427 Injector Storage Standard

#### (1) Choose a suitable storage place

SHUMATT

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area and Car dry.

all the

#### (2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

#### (3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

#### (4) Stack Properly

and and a start a start a start . After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

It is forbidden to leave the injector exposed in the air for a long time.

It is forbidden to store acid, alkali, salt and other substances together with the injector,

A The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information was start start



**Telephone:** +86-755-23215133

Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

SPORT

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

THE THE THE ATT A THE ATT AND A THE ATT AND A THE ATT AND A THE ATT A

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

58.<sup>578</sup>

Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd **After-sales Service Address:** Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: <u>1.10.326-4700 Injector Warranty Instructions</u>)

5.2	. Contact Information	1	The The The D	6	5
No.	Name	WeChat/ WhatsApp	Email	Facebook	YouTube
1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li
2	lvy	+86-18025309821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY
3. <sub>3</sub> 70	Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie
<b>7</b> 30	🐃 Ada 🐄	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca
10	Fric AS	+86 18319033618	sales3@shumatt.com	All All	de de
11	<sup>™</sup> Wayne <sup>™</sup> ( Joaquín en español )	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt
12	Sylvia	+86 18312499884	sales6@shumatt.com	i na	all with
S. C.	and the second second	Visit http://shumatt.com to ob	otain the latest information of salesme	en and and a second	
		PS: Shumatt's sales-men's e	mails are all end with @shumatt.com		

#### 6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "*C7 Injector 383-9427 Technical File*" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "*C7 Injector 383-9427 Technical File*" in any way. At the same time, any conditions to spread, re-post, display the contents of "*C7 Injector 383-9427 Technical File*" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "*C7 Injector 383-9427 Technical File*" will violate the "*Copyright Law of the People's Republic of China*" and other laws and regulations and the provisions of relevant international conventions.