

3973228 Fuel Pump CCR1600 Series Technical File

SKU1: G1Y60003973228

SKU2: Y2L33973228K6K





3973228 Fuel Pump CCR1600 Series Technical File

Content

1. 3973228 Fuel Pump Introduction	2
1.1. 3973228 Fuel Pump Basic Information	2
1.2. 3973228 Fuel Pump Common Part Number	2
1 3 3973228 Fuel Pump Parameter	2
1.4. 3973228 Fuel Pump Specifications And Dimensions	2
1.5. 3973228 Fuel Pump Quality Control	2
1.6. 3973228 Fuel Pump Customized Service	
1.7. 3973228 Fuel Pump Packing List and Package Size	3
1.8. 3973228 Fuel Pump Testing Standard and Certificate	5
1.9. 3973228 Fuel Pump Warranty Instructions	5
1.10. 3973228 Fuel Pump Manufacturer	6
2. 3973228 Fuel Pump Technical Support	6
2.1. 3973228 Fuel Pump Use location	6
2.2. 3973228 Fuel Pump Installation	7
2.3. 3973228 Fuel Pump Not Working Normally	8
2.4. 3973228 Fuel Pump Causes of Being Damaged	
2.5. 3973228 Fuel Pump Technical Support Obtaining Methods	9
3. 3973228 Fuel Pump Purchase and Delivery	9
3.1. 3973228 Fuel Pump Purchase Payment Term	9
3.2. 3973228 Fuel Pump Main Sales Markets	9
3.3. 3973228 Fuel Pump Declaration Requirements	9
3.4. 3973228 Fuel Pump Shipping Ways	9
3.5. 3973228 Fuel Pump Lead Time	9
3.6. 3973228 Fuel Pump Logistics Time for Destination Out of China's Areas	10
3.7. 3973228 Fuel Pump Packing	10
4. 3973228 Fuel Pump Storage Standard	11
5. Company Information	12
5.1. Company Introduction	12
5.2 Salesmen's Contact Information	13
6. Copyright Statement	13
SHARKL	100 TO
str.,	2000 July
<i>a</i>	565
SHIRKLE	Maria Shir
THE STATE OF	Table Alle
alson. Alson,	70,000
ואר	. TASSON.
ac' .	. 4000000

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumatt.com



3973228 Fuel Pump CCR1600 Series Technical File

1. 3973228 Fuel Pump Introduction

1.1. 3973228 Fuel Pump Basic Information

Title	3973228 CCR1600 Series Fuel Pump	Quality
SKU1	G1Y60003973228	China Made New
SKU2	Y2L33973228K6K	Original New

1.2. 3973228 Fuel Pump Common Part Number

(1) Fuel Pump Exchange Information

Fuel Pump Part Number	Car Model	Compatible Number	Compatible Number	OE Number
3973228	KOMATSU	4954200	5311171	6745-71-1150

(2) Fuel Pump Application Information

Vehicle Brand	Car Model	Engine Model	Production Date	Power (KW)	Horse Power	Emission (L)	Cylinder	Power Source (V)
1,000	/	es / ess	/.	at /	c /_c	/	ati / ati	, <u>/</u> ,

(3) Fuel Pump Common Writing

3973228, 4954200, 5311171, 6745-71-1150

1.3. 3973228 Fuel Pump Parameter

Adaptation System: Common Rail System

Fuel Pump Series: CCR1600 Series

Fuel Pump Type: High Pressure Pump, CCR1600 System

1.4. 3973228 Fuel Pump Specifications And Dimensions

Fuel Pump Size: 39cm* 32cm *21 cm

Fuel Pump Net Weight: 15kg Fuel Pump Gross Weight: 16kg

Fuel Pump Quality: Original New/ China Made New Fuel Pump Package Size: 40cm* 33cm *22cm Fuel Pump Type: High Pressure Pump Fuel Pump

Fuel Pump MOQ: 1 Pieces

1.5. 3973228 Fuel Pump Quality Control

(1) Fuel Pump Testing

ation, at the

All fuel pumps are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com



(2) Fuel Pump Assembling

For the quality control of the Fuel Pump production and installation process, our company strictly follows the standard product installation data and product installation steps to install.

(3) Fuel Pump Inspection

The factory inspection of the fuel pumps is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel pumps for more than three times for factory inspection, and the fuel pumps installation testing environment are progressed in dust-free workshop.

1.6. 3973228 Fuel Pump Customized Service

(1) Fuel Pump Customized Service Coverage: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, fuel pump internal packaging, fuel pump external packaging and labels customized, etc.



(2) Fuel Pump Customized Service Requirements:

The quantity of customized fuel pump shall not be less than 10 pieces.

The quantity of customized fuel pump packages shall not be less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

▲ Once the customized fuel pump is sold, it cannot be returned or exchanged if there are no quality problems.

1.7. 3973228 Fuel Pump Packing List and Package Size

(1) Fuel Pump Spare Parts List

NO.	1	2	3
Shaper Control of the state of	Shunati		
Name	Fuel Pump Assembly	Blue Anti-Rust Bag	Lining
Description	Fuel pump part number: 3973228	Prevent fuel pump from rusting	Prevent the fuel pump from being damaged by external forces

Mob/Whatsapp: +86 13410541523

Email: ruby@shumatt.com

© 2025 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133

Website: www.shumatt.com



NO.	4	5	6
SiPicture, No.			
Name	Fuel Pump Packaging Box	Fuel Pump Protective Cover	A A A
Description	Place the fuel pump and accessories	Protect the fuel pump hole from contamination and blockage	

The state of the s Minors are prohibited from using the fuel pump assembly, O-ring, fuel inlet protective cover, fuel pump shell protective cover, oil return protective cover, VCI anti-rust bag, and bubble bag to avoid personal injury.

• O-rings and repair kits are one-time installation accessories and need to be replaced when installed again.

▲ Oil inlet protective cover, fuel pump shell protective cover, and oil return protective cover are recyclable accessories and can be reused.

 $oldsymbol{\Lambda}$ VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.

A The fuel pump and the installation part duct must be treated with appropriate sealing oil during The state of the s



Tel: +8675523215133 Mob/Whatsapp: +86 13410541523 Email: ruby@shumatt.com Website: www.shumatt.com



No.	Name					Fue	l Pump P	acking S	ize (cm)	
APT - 50	- 57	5/10/	SX	£3,000	Star	-870	-575	ST	SA	SX	- 6
1		Fuel Pu	mp Box				28	3*22*25			
240	07		Left.	247			340	340	240	240	

1.8. 3973228 Fuel Pump Testing Standard and Certificate

Shumatt can provide the factory quality inspection test report of each fuel pump to ensure that each fuel pump delivered meets the engine performance indicators.



1.9. 3973228 Fuel Pump Warranty Instructions

(1) Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the fuel pump inspection equipment when the fuel pump is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) Fuel Pump Warranty Coverage

Within 15 days after customer receives the 3973228 fuel pump, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the 3973228 fuel pump has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the fuel pump house has obvious scratches, it can only be repaired and it will be returned as it is if

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Website: www.shumatt.com

Email: ruby@shumatt.com



the product is confirmed to be fault-free.

 $oldsymbol{oldsymbol{\Delta}}$ Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) Fuel Pump Out of Warranty Coverage

1700

- 1 The warranty period has expired.
- 2 Fuel pump failure caused by high temperature, high pressure, humidity, rain and snow, salinealkali land, earthquake, and used in abnormal environment.
 - 3 Customer disassembles or repairs the fuel pump personally resulting in damage to the Fuel Pump.
- Fuel pump damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire).
- 5 Fuel pump failure or fuel pump damage caused by non-fuel pump design, technology, manufacturing, quality, and other issues.
 - Fuel pump failure due to system pressure exceeding system approved pressure.
- Fuel pump failure caused by system voltage exceeding approved voltage.
- 8 Fuel pump failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in AND STATE OF the system fuel exceeding the standard requirements.
- 9 Fuel pump failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).
- Fuel pump failure caused by not following the installation angle specified in the vehicle engine maintenance manual.
- 11 Fuel pump failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.
- 12. Fuel pump failure caused by failure to replace consumable parts as specified in the vehicle engine they are alone at the maintenance manual.
- 13 Fuel pump failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.
- 14 Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the Fuel pump connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.10. 3973228 Fuel Pump Manufacturer

Fuel Pump Manufacturer: Shenzhen Shumatt Technology Co., Ltd

2. 3973228 Fuel Pump Technical Support


2.1. 3973228 Fuel Pump Use location

NO.	Name
SHOWER SHOWER SHOWER WASHING THE SHOWER SHOWER IN	Nameplate, Logo, Part Number

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com





(1) 3973228 Fuel Pump Installation Precautions:

A The replacement of the fuel pump must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual.

Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the fuel pump, the fitting clearance of the fuel pump connection, the installation angle and tightening torque of the fuel pump, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the fuel pump.

When installing the fuel pump on the engine, it is necessary to clean the engine cylinder block, cylinder head and other parts connected to the fuel pump and ensure that they are clean and free of dust, carbon deposits, water, rust spots, etc.

A Failure to replace the new sealing ring gasket may lead to: fuel pump deformation, fuel leakage, air

Tel: +8675523215133 Mob/Whatsapp: +86 13410541523 Email: ruby@shumatt.com Website: www.shumatt.com



leakage, serious damage to the fuel pump, causing the fuel pump to break and cause engine damage.

⚠ When installing the fuel pump on the engine, please carefully check that the parts related to the SHOP! installation of the fuel pump, such as the fuel pump pressure plate, screws, push rods and other accessories are not deformed, and strictly follow the operating procedures in the engine maintenance manual for installation.

PARTY DESIGNATION OF THE TAXABLE SECTION OF TAXABLE It is forbidden to expose the fuel pump for a long time in an environment with severe dust pollution and corrosion to iron products.

 $oldsymbol{\mathbb{A}}$ It is forbidden to expose the fuel pump for a long time in a strong magnetic field environment.

2.3. 3973228 Fuel Pump Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump's oil supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel pump of the vehicle.
- (5) The long-term placement of the fuel pump causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.

Before installing, carefully check whether other components in the common rail system exceCCR1600 the fuel pump are damaged to prevent the fuel pump from not working properly after being replaced.

ONE STATE SOUTH SOUTH SOUTH SOUTH

- 2.4. 3973228 Fuel Pump Causes of Being Damaged
 (1) Didn't operate process (1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the fuel pump.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the fuel pump, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide $\partial \chi_{o}$ impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the fuel pump.
- (4) The abrasion of the fuel pump produces iron powder and aluminum powder enter the fuel pump and cause damage to the fuel pump.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel pump and causing damage to the fuel pump.
- (6) The fuel pump is damaged due to replacement or adjustment of the relevant parts of the fuel pump. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the fuel pump fails to meet the original standard.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email: ruby@shumatt.com Website: www.shumatt.com

© 2025 Shenzhen Shumatt Technology Co., Ltd

8 / 15



- (7) The engine is overheated and overloaded for a long-time working result in damage to the fuel pump.
- (8) The fuel pump will be damaged naturally at the end of its working life.
- (9) The fuel pump is magnetized (fuel pump parts' magnetic exceeded) causing the fuel pump to not work

 $oldsymbol{\mathbb{A}}$ Before replacing the fuel pump, please check the engine parts carefully according to the engine maintenance manual to avoid the Fuel Pump being damaged again after replacement.

2.5. 3973228 Fuel Pump Technical Support Obtaining Methods

- (1) Fuel pump technical file, visit http://shumatt.com to get the technical file.
- (2) Fuel pump technical videos

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV_mAfxh_Hu-aw_to get_the technical videos, constantly follow can get more information.

Shumatt: Visit http://shumatt.com to get the technical videos.

(3) Fuel pump information query software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit http://shumatt.com to get the download and installation tutorial.

(4) Search the fuel pump test data through TruckBook Parts EPC APP.

3. 3973228 Fuel Pump Purchase and Delivery

3.1. 3973228 Fuel Pump Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2. 3973228 Fuel Pump Main Sales Markets

Fuel Pump Main Sales Markets: Asia, Europe, North America, South America, Africa etc.

3.3. 3973228 Fuel Pump Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

and the

-02TT

3.4. 3973228 Fuel Pump Shipping Ways

Destination in China Areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations Out of China's Areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5. 3973228 Fuel Pump Lead Time

Philips Lead Time: Send out within 3 - 7 working days after receiving payment (ExceCCR1600 for special products and special cases). THE THE THE PERSON THE STATE OF THE PERSON THE STATE OF T

et Paris

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com



3.6. 3973228 Fuel Pump Logistics Time for Destination Out of China's Areas

DHL Logistics Time:

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries	200-
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days	50°04

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	ST UK ST	5-7Days	EgyCCR1600	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	177 Jet 178	A	775gg 1775gg 77	mail Land



The logistics time is for reference only and is subject to the actual arrival.

3.7. 3973228 Fuel Pump Packing

Domestic Express Packaging: Usually wrapped in waterproof scotch tape, such as picture No. 1.

International Express Packaging: Wrapped with waterproof yellow tape after wrapping the black protective film, such as picture No. 2.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 3, also, the products can be packaged according to customers' requirements.



The packing tray is made of plastic and can be recycled.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email: ruby@shumatt.com Website: www.shumatt.com

THE THE PERMIT SHEET SHEET SHEET SHEET SHEET SHEET SHEET SHEET

 $e^{i \sqrt{2} \sqrt{N}}$

Shenzhen Shumatt Technology Co., Ltd

Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



Pic No. 1 Domestic express packaging: Wrapped with Transparent tape



Pic No. 2 International express packaging: Wrapped with yellow tape after wrapping black protective film



Pic No. 3

Pallet shipment: Use pallets that meet export requirements and wrap with white plastic wrap and tie.

4. 3973228 Fuel Pump Storage Standard

(1) Choose a Suitable Storage Place

The warehouse and cargo yard where the fuel pump is stored should be keCCR1600 clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acids, alkali, salt, and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir

(2) Strict Requirements of Warehousing

© 2025 Shenzhen Shumatt Technology Co., Ltd

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com



Strict inspections should be carried out when the fuel pumps are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ashes, and other dirt, remove the rust and do anti-rust treatment in time. Packaged fuel pumps must be protected from damage.

(3) Keep The Warehouse Dry And Preventing Moisture

The relative humidity is usually below 70% for the fuel pumps placed in the room, and the corrosion of the fuel pumps is significantly reduced. 200 300

Fuel pumps must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the fuel pump is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the fuel pump from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse.

If the fuel pump package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.



It is forbidden to leave the fuel pump exposed in the air for a long time.



It is forbidden to store acids, alkalis, salts, and other substances together with the fuel pump.



The unpacked fuel pump must be rust-proof during secondary storage.

5. Company Information



5.1. Company Introduction

Chinese Name: 深圳市舒马特科技有限公司

English Name: Shenzhen Shumatt Technology Co., Ltd

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email: ruby@shumatt.com Website: www.shumatt.com

© 2025 Shenzhen Shumatt Technology Co., Ltd

12 / 15



☐ Mob Phone/WeChat: +86-13410541523

HK Telephone: +852-67653519

Telephone: +86-755-23215133

Email: ruby@shumatt.com

Website: www.shumatt.com

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Exit C, Qiao Touxi Metro Station, NO. 66 Chongqing Road, Fuhai Avenue, Bao'an District, Shenzhen, China Mainland

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: 1.9. 3973228 Fuel Pump Warranty Instructions)

5.2. Salesmen's Contact Information

No.	Name	WeChat/WhatsApp	Email				
1	Ruby	+86-13410541523	ruby@shumatt.com				
2,000	Party and the second	+86-18025299821	sales@shumatt.com				
3	Rebecca	+86-18025349821	sales01@shumatt.com				
4	Janny Janny	+86-18028749821	sales02@shumatt.com				
5	Sam	+86-13316859821	Sales8@shumatt.com				
6	Natalie	+86- 18938945856	sales15@shumatt.com				
7 0000	Ada	+86-1342286353	sales5@shumatt.com				
8	Hison Li	+86-18318811871	web@shumatt.com				
9	Mecca	+86-18938948618	sales11@shumatt.com				
10	Fric Fric	+86 18319033618	sales3@shumatt.com				
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com				
12	Sylvia	+86 18312499884	sales6@shumatt.com				
05	Visit http://shumatt.com to obtain the latest information of salesmen						
JSm.	PS: Shumatt's sales	men's emails are all end with	@shumatt.com				

6. Copyright Statement


The copyright of any contents (including but not limited to parameters, data, text, charts, images,

Mob/Whatsapp: +86 13410541523Tel: +8675523215133Email: ruby@shumatt.comWebsite: www.shumatt.com

2 -----



sounds, or videos, etc.) provided in "3973228 Fuel Pump CCR1600 Series Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "3973228 Fuel Pump CCR1600 Series Technical File" in any way. At the same time, any conditions to spread, repost, display the contents of "3973228 Fuel Pump CCR1600 Series Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "3973228 Fuel Pump CCR1600 Series Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.



Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email: <u>ruby@shumatt.com</u> Website: <u>www.shumatt.com</u>