



17x7x1MM Injector Nozzle Copper Washer Shim Technical File

SKU: G1Y1006520YZDP



17x7x1MM Injector Nozzle Copper Washer Shim Technical File

Content

| | |
|--|----|
| 1. 17x7x1MM Injector Nozzle Copper Washer Shim Introduction | 1 |
| 1.1. 17x7x1MM Injector Nozzle Copper Washer Shim Basic Information | 1 |
| 1.2. 17x7x1MM Injector Nozzle Copper Washer Shim Common Part Number | 1 |
| 1.4. 17x7x1MM Injector Nozzle Copper Washer Shim Specifications and Dimensions | 1 |
| 1.5. 17x7x1MM Injector Nozzle Copper Washer Shim Quality Control | 1 |
| 1.6. 17x7x1MM Injector Nozzle Copper Washer Shim Customized Service | 2 |
| 1.7. 17x7x1MM Injector Nozzle Copper Washer Shim Packing List and Package Size | 2 |
| 1.8. 17x7x1MM Injector Nozzle Copper Washer Shim Testing Standard and Certificate | 4 |
| 1.9. 17x7x1MM Injector Nozzle Copper Washer Shim Warranty Instructions | 4 |
| 1.10. 17x7x1MM Injector Nozzle Copper Washer Shim Manufacturer | 6 |
| 2. 17x7x1MM Injector Nozzle Copper Washer Shim Technical Support | 6 |
| 2.1. 17x7x1MM Injector Nozzle Copper Washer Shim Installation Precautions | 6 |
| 2.2. 17x7x1MM Injector Nozzle Copper Washer Shim Not Working Normally | 6 |
| 2.3. 17x7x1MM Injector Nozzle Copper Washer Shim Causes of Being Damaged | 7 |
| 2.4. 17x7x1MM Injector Nozzle Copper Washer Shim Technical Support Obtaining Methods | 7 |
| 3. 17x7x1MM Injector Nozzle Copper Washer Shim Purchase and Delivery | 8 |
| 3.1. 17x7x1MM Injector Nozzle Copper Washer Shim Purchase Payment Term | 8 |
| 3.2. 17x7x1MM Injector Nozzle Copper Washer Shim Main Sales Markets | 8 |
| 3.3. 17x7x1MM Injector Nozzle Copper Washer Shim Declaration Requirements | 8 |
| 3.4. 17x7x1MM Injector Nozzle Copper Washer Shim Shipping Ways | 8 |
| 3.5. 17x7x1MM Injector Nozzle Copper Washer Shim Lead time | 8 |
| 3.6. 17x7x1MM Injector Nozzle Copper Washer Shim Logistics Time for Destination Out of China's Areas | 8 |
| 3.7. 17x7x1MM Injector Nozzle Copper Washer Shim Packing | 9 |
| 4. 17x7x1MM Injector Nozzle Copper Washer Shim Storage Standard | 10 |
| 5. Company Information | 10 |
| 5.1. Company Introduction | 11 |
| 5.2. Salesmen's Contact Information | 11 |
| 6. Copyright Statement | 12 |

17x7x1MM Injector Nozzle Copper Washer Shim Technical File

1. 17x7x1MM Injector Nozzle Copper Washer Shim Introduction

1.1. 17x7x1MM Injector Nozzle Copper Washer Shim Basic Information

| Title | 17x7x1MM Injector Nozzle Copper Washer Shim | Quality |
|-------|---|----------------|
| SKU | G1Y1006520YZDP | China Made New |

1.2. 17x7x1MM Injector Nozzle Copper Washer Shim Common Part Number

(1) Injector Nozzle Copper Washer Shim Compatible With Injector Part Number

| Injector Part Number | Injector Part Number |
|----------------------|----------------------|
| / | / |

(2) Injector Nozzle Copper Washer Shim Application Information

| Engine | OE Number |
|--------|-----------|
| / | / |

(3) Injector Nozzle Copper Washer Shim Part Number Common Writing

17x7x1MM

1.3. 17x7x1MM Injector Nozzle Copper Washer Shim Parameter

Adaptation System: Common Rail System

Injector Nozzle Copper Washer Shim Series: /

Injector Nozzle Copper Washer Shim Type: Electromagnetic

1.4. 17x7x1MM Injector Nozzle Copper Washer Shim Specifications and Dimensions

Injector Nozzle Copper Washer Shim Size: 9cm*9cm*1cm

Injector Nozzle Copper Washer Shim Net Weight: 180g

Injector Nozzle Copper Washer Shim Gross Weight: 370g

Injector Nozzle Copper Washer Shim Quality: China Made New

Injector Nozzle Copper Washer Shim Box Size: 12*cm* 11cm *4cm

Injector Nozzle Copper Washer Shim Type: High Pressure Common Rail Injector Nozzle Copper Washer Shim

Injector Nozzle Copper Washer Shim MOQ: 100 Pieces

1.5. 17x7x1MM Injector Nozzle Copper Washer Shim Quality Control

(1) Injector Nozzle Copper Washer Shim Testing

All injector nozzle copper washer shim are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Nozzle Copper Washer Shim Assembling

Quality control during the production and installation of injector nozzle copper washer shims is strictly

enforced by our company in accordance with standard product installation data and procedures. This includes testing the injector nozzle copper washer shim stroke, tightening the injector nozzle copper washer shim solenoid valve torque, and tightening the injector nozzle copper washer shim and injector nozzle torque.

(3) Injector Nozzle Copper Washer Shim Inspection

The factory inspection of the injector nozzle copper washer shim is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same injector nozzle copper washer shim for a total of no less than three times for factory inspection, and the injector nozzle copper washer shim installation testing environment are progressed in dust-free workshop.

1.6. 17x7x1MM Injector Nozzle Copper Washer Shim Customized Service

(1) Injector Nozzle Copper Washer Shim Customized Service: Meet the customized needs of OEM manufacturers for body engraving, logo engraving, internal packaging of injector nozzle copper washer shims, external packaging of injector nozzle copper washer shims, and labels.

| | |
|--|--|
|  | / |
| Injector Nozzle Copper Washer Shim Packaging | Injector Nozzle Copper Washer Shim Label |

(2) Injector Nozzle Copper Washer Shim Customized Service Requirements:

Customized injector nozzle copper washer shim packages no less than **100 pieces**

Customized injector nozzle copper washer shim sales are not less than **1000 pieces**

When the customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

⚠ Once the customized injector nozzle copper washer shim is sold, it cannot be returned or exchanged if there is no quality problems.

1.7. 17x7x1MM Injector Nozzle Copper Washer Shim Packing List and Package Size

(1) Injector Nozzle Copper Washer Shim Spare Parts List

| No. | 1 | 2 | 3 |
|-------------|---|---|---|
| Image |  |  |  |
| Name | Injector Nozzle Copper Washer Shim Assembly | Copper Washer Shim Inner Diameter | Copper Washer Shim Outer Diameter |
| Description | injector nozzle copper washer shim part number: 17x7x1MM | Inner diameter measured 17mm | Outer diameter measured 7mm |

| No. | 4 | 5 | 6 |
|-------------|--|---|---|
| Image | | / | / |
| Name | injector nozzle copper washer shim Thickness | / | / |
| Description | Thickness measurement 1mm | / | / |

- ▲ Minors are prohibited from using injector nozzle copper washer shim assemblies, VCI rust-proof papers to prevent personal injury.
- ▲ The injector nozzle copper washer shim is a one-time installation accessory and needs to be replaced when reinstalling.
- ▲ VCI rust-proof papers are made of non-degradable materials and should be disposed of properly after use.
- ▲ When installing the injector nozzle copper washer shim and mounting parts guide, apply an appropriate amount of sealing oil.

(2) Injector Nozzle Copper Washer Shim Box Size



| No. | Name | Injector Nozzle Copper Washer Shim Packing Size(cm) |
|-----|--|---|
| 1 | Injector Nozzle Copper Washer Shim Packaging Box | 17*15*1 |

1.8.17x7x1MM Injector Nozzle Copper Washer Shim Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector nozzle copper washer shim to ensure that each injector nozzle copper washer shim delivered meets the engine performance indicators.

| BOTEN | | 测试报告 | 4.05.2019 10:42:09 |
|---|-------|------------|--------------------|
| 承检企业: _____ | | | |
| 电话: | _____ | 地址: | _____ |
| 传真: | _____ | 检测人: | _____ |
| 客户单位: | _____ | 送检单位: | _____ |
| 电话: | _____ | 客户姓名: | _____ |
| 传真: | _____ | _____ | _____ |
| 检测描述: | _____ | | |
| 客户名称: | _____ | 客户地址: | _____ |
| 型号-零件号: | _____ | | |
| 检测内容: | _____ | | |
| 检测结果 | | | |
| 检测器型号: CG6000-GS11 | 检测项目 | 检测结果 | 检测示意图 |
| LEAK TEST: | OK | —±— | ✓ |
| Back: | OK | —+— | ✓ |
| MAX:MM: | OK | 142.3±1.5 | OK |
| Max: | 201.5 | 218.5±14.4 | OK |
| TL: | 184 | 24.6±8.5 | OK |
| UL: | 14.1 | 15.2±4.8 | OK |
| VE: | 47 | 4.5±1.8 | OK |
| <input type="checkbox"/> 检测序号: _____ | | | |
| <input type="checkbox"/> <input type="checkbox"/> 检修前 <input type="checkbox"/> <input type="checkbox"/> 检修后 | | | |

1.9. 17x7x1MM Injector Nozzle Copper Washer Shim Warranty Instructions

(1) Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector nozzle copper washer shim inspection equipment when the injector nozzle copper washer shim is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1. Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) Injector Nozzle Copper Washer Shim Warranty Coverage

Within 15 days after customer receives the 17x7x1MM injector nozzle copper washer shim, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;



If the 17x7x1MM injector nozzle copper washer shim has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector nozzle copper washer shim house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

⚠ Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) Injector Nozzle Copper Washer Shim Out of Warranty Coverage

- ① The warranty period has expired.
- ② Injector nozzle copper washer shim failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.
- ③ Customer disassembles or repairs the injector nozzle copper washer shim personally resulting in damage to the injector nozzle copper washer shim.
- ④ Injector nozzle copper washer shim damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire).
- ⑤ Injector nozzle copper washer shim failure or injector nozzle copper washer shim damage caused by non-injector nozzle copper washer shim design, technology, manufacturing, quality, and other issues.
- ⑥ Injector nozzle copper washer shim failure due to system pressure exceeding system approved pressure.
- ⑦ Injector nozzle copper washer shim failure caused by system voltage exceeding approved voltage.
- ⑧ Injector nozzle copper washer shim failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.
- ⑨ Injector nozzle copper washer shim failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).
- ⑩ Injector nozzle copper washer shim failure caused by not following the installation angle specified in the vehicle engine maintenance manual.
- ⑪ Injector nozzle copper washer shim failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.
- ⑫ Injector nozzle copper washer shim failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.
- ⑬ Injector nozzle copper washer shim failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.
- ⑭ Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the injector nozzle copper washer shim connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.



1.10. 17x7x1MM Injector Nozzle Copper Washer Shim Manufacturer

Injector Nozzle Copper Washer Shim Manufacturer: Shenzhen Shumatt Technology Co., Ltd

2. 17x7x1MM Injector Nozzle Copper Washer Shim Technical Support

2.1. 17x7x1MM Injector Nozzle Copper Washer Shim Installation Precautions

- (1) The replacement of the injector nozzle copper washer shim must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual.
- (2) Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector nozzle copper washer shim, the fitting clearance of the injector nozzle copper washer shim connection, the installation angle and tightening torque of the injector nozzle copper washer shim, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector nozzle copper washer shim.
- (3) When installing the injector nozzle copper washer shim on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the injector nozzle copper washer shim, and ensure that there is no dust, carbon deposits, water, rust spots, etc.
- (4) Before installation, check whether the injector nozzle copper washer shim and nozzle sealing gasket have been replaced and installed on the injector nozzle copper washer shim.
- (5) When installing the injector, apply lubricant between the injector, nozzle seal shim, and O-ring.
- (6) Failure to replace the gasket with a new one can lead to deformation of the injector cap, nozzle, and nozzle orifice, oil and air leakage, and serious damage to the injector, including nozzle breakage and engine damage.
- (7) When installing the injector nozzle copper washer shim on the engine, carefully check that the components related to the installation, such as the injector nozzle copper washer shim pressure plate, screws, push rods, and other accessories, are not deformed, and strictly follow the operating procedures in the engine repair manual for installation.
- (8) It is forbidden to operate the bare injector nozzle copper washer shim for a long time in an environment with serious dust pollution and corrosion to iron products.
- (9) It is forbidden to operate the bare injector nozzle copper washer shim for a long time in a strong magnetic field environment.

2.2. 17x7x1MM Injector Nozzle Copper Washer Shim Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump's oil supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the injector nozzle copper washer shim of the vehicle.
- (5) The long-term placement of the injector nozzle copper washer shim causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.

⚠ Before installing, carefully check whether other components in the common rail system except the injector nozzle copper washer shim are damaged to prevent the injector nozzle copper washer shim from not working properly after being replaced.

2.3. **17x7x1MM Injector Nozzle Copper Washer Shim Causes of Being Damaged**

- (1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the injector nozzle copper washer shim.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector nozzle copper washer shim, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector nozzle copper washer shim.
- (4) The abrasion of the injector nozzle copper washer shim produces iron powder and aluminum powder enter the injector nozzle copper washer shim and cause damage to the injector nozzle copper washer shim.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the injector nozzle copper washer shim and causing damage to the injector nozzle copper washer shim.
- (6) The injector nozzle copper washer shim is damaged due to replacement or adjustment of the relevant parts of the injector nozzle copper washer shim. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector nozzle copper washer shim fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long-time working result in damage to the injector nozzle copper washer shim.
- (8) The injector nozzle copper washer shim will be damaged naturally at the end of its working life.
- (9) The injector nozzle copper washer shim is magnetized (injector nozzle copper washer shim parts' magnetic exceeded) causing the injector nozzle copper washer shim to not work properly.

⚠ Before replacing the injector nozzle copper washer shim, please check the engine parts carefully according to the engine maintenance manual to avoid the injector nozzle copper washer shim being damaged again after replacement.

2.4. **17x7x1MM Injector Nozzle Copper Washer Shim Technical Support Obtaining Methods**

- (1) Injector Nozzle Copper Washer Shim Technical File , visit <http://shumatt.com> to get the technical file.
- (2) Injector Nozzle Copper Washer Shim Technical Videos

Facebook: Visit <https://www.facebook.com/hison.li> to get the technical videos, constantly follow can get more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV_mAfxh_Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit <http://shumatt.com> to get the technical videos.

- (3) Injector Nozzle Copper Washer Shim Information Query Software



TruckBook Parts EPC APP, Android/Apple App Store download and install, visit <http://shumatt.com> to get the download and installation tutorial

(4) Search the Injector Nozzle Copper Washer Shim Test Data Through TruckBook Parts EPC APP.

3.17x7x1MM Injector Nozzle Copper Washer Shim Purchase and Delivery

3.1.17x7x1MM Injector Nozzle Copper Washer Shim Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

⚠ Please contact our salesmen for specific payment information.

3.2.17x7x1MM Injector Nozzle Copper Washer Shim Main Sales Markets

Injector nozzle copper washer shim main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3.17x7x1MM Injector Nozzle Copper Washer Shim Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4. 17x7x1MM Injector Nozzle Copper Washer Shim Shipping Ways

Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5. 17x7x1MM Injector Nozzle Copper Washer Shim Lead time

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and special cases) .

3.6. 17x7x1MM Injector Nozzle Copper Washer Shim Logistics Time for Destination Out of China's Areas

DHL Logistics Time :

| Country or Region of Departure | Hong Kong, China | Other Countries or Regions of Asia | Australia and New Zealand | Europe | America | Other Countries |
|--------------------------------|------------------|------------------------------------|---------------------------|--------|-----------|-----------------|
| China's Mainland | 7 Days | 7 Days | 8 Days | 8 Days | 8-12 Days | 7-10 Days |

UPS Logistics Time: Country or Region of Departure: China's Mainland

| Country of Destination | Estimated Arrival Time | Country of Destination | Estimated Arrival Time | Country of Destination | Estimated Arrival Time |
|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| Japan | 3 Days | UK | 5-7 Days | Egypt | 5-7 Days |
| Turkey | 5-7 Days | Singapore | 3 Days | Switzerland | 5-7 Days |
| Bahrain | 5-7 Days | Latvia | 7-10 Days | New Zealand | 7-10 Days |
| Sri Lanka | 5-7 Days | Thailand | 3 Days | Austria | 5-7 Days |

| | | | | | |
|-------------|-----------|-------------|-----------|----------------------|-----------|
| Romania | 5-7 Days | Vietnam | 3-5 Days | Estonia | 5-7 Days |
| Malaysia | 3-5 Days | Israel | 5-7 Days | Mexico | 7-10 Days |
| France | 5-7 Days | America | 5-7 Days | United Arab Emirates | 5-7 Days |
| Italy | 5-7 Days | Netherlands | 5-7 Days | Bengal | 7-10 Days |
| Lebanon | 5-7 Days | Philippine | 3-5 Days | Greece | 7-10 Days |
| South Korea | 3 Days | Spain | 5-7 Days | Myanmar | 5-7 Days |
| Canada | 5-7 Days | Germany | 5-7 Days | Saudi Arabia | 7-10 Days |
| Portugal | 5-7 Days | Australia | 5-7 Days | South Africa | 7-10 Days |
| Denmark | 5-7 Days | Belgium | 5-7 Days | Ukraine | 7-10 Days |
| India | 7-10 Days | Qatar | 7-10 Days | Poland | 5-7 Days |
| Indonesia | 3-5 Days | Morocco | 7-10 Days | Pakistan | 7-10 Days |
| Kuwait | 7-10 Days | / | / | / | / |

▲ The logistics time is for reference only, subjects are according to the actual arrival.

3.7. 17x7x1MM Injector Nozzle Copper Washer Shim Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.1.


International express packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 2.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 3, also, the products can be packaged according to customers' requirements.

▲ The packing tray is made of plastic and can be recycled.

▲ Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

▲ Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.

| No. | 1 | 2 | 3 |
|-------|---|--|---|
| Image |  |  |  |
| Name | Domestic Express Packaging | International Express Packaging | Pallet Shipping |

| | | | |
|--------------------|-----------------------------|---|---|
| Description | Wrapped by transparent tape | Wrapped with yellow tape after wrapping black protective film | Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties |
|--------------------|-----------------------------|---|---|

4.17x7x1MM Injector Nozzle Copper Washer Shim Storage Standard

(1) Choose a suitable storage place

The warehouse and cargo yard where the injector nozzle copper washer shim is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acids, alkalis, salts and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry.

(2) Strict requirements of warehousing

Strict inspections should be carried out when the injector nozzle copper washer shims are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injector nozzle copper washer shim must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the injector nozzle copper washer shims placed in the room, and the corrosion of the injector nozzle copper washer shims is significantly reduced.

Injector nozzle copper washer shims must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the injector nozzle copper washer shim is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector nozzle copper washer shim from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the injector nozzle copper washer shim package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

- ▲ It is forbidden to leave the injector nozzle copper washer shim exposed in the air for a long time.
- ▲ It is forbidden to store acid, alkali, salt and other substances together with the injector nozzle copper washer shim.
- ▲ The unpacked injector nozzle copper washer shim must be rust-proof during secondary storage.

5. Company Information



5.1. Company Introduction

Chinese Name: 深圳市舒马特科技有限公司

English Name: Shenzhen Shumatt Technology Co., Ltd

❑ **Mob Phone/WeChat:** +86-13410541523

❑ **HK Telephone:** +852-67653519

❑ **Telephone:** +86-755-23215133

❑ **Email:** ruby@shumatt.com

❑ **Website:** www.shumatt.com

❑ **Shenzhen Office:** 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

❑ **Shenzhen Office:** Exit C, Qiao Touxi Metro Station, NO. 66 Chongqing Road, Fuhai Avenue, Bao'an District, Shenzhen, China Mainland

❑ **Hong Kong Office:** Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

❑ **After-sales Service Address:** Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: [1.9. 17x7x1MM Injector Nozzle Copper Washer Shim Warranty Instructions](#))

5.2. Salesmen's Contact Information

| No. | Name | WeChat/WhatsApp | Email |
|-----|------|-----------------|--|
| 1 | Ruby | +86-13410541523 | ruby@shumatt.com |

Mob/WhatsApp: +86 13410541523

Email : ruby@shumatt.com

© 2026 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133

Website : www.shumatt.com



| | | | |
|----|------------------------------|-----------------|---------------------|
| 2 | Ivy | +86-18025299821 | sales@shumatt.com |
| 3 | Rebecca | +86-18025349821 | sales01@shumatt.com |
| 4 | Janny | +86-18028749821 | sales02@shumatt.com |
| 5 | Sam | +86-13316859821 | Sales8@shumatt.com |
| 6 | Natalie | +86-18938945856 | sales15@shumatt.com |
| 7 | Ada | +86-1342286353 | sales5@shumatt.com |
| 8 | Hison Li | +86-18318811871 | web@shumatt.com |
| 9 | Mecca | +86-18938948618 | sales11@shumatt.com |
| 10 | Eric | +86-18319033618 | sales3@shumatt.com |
| 11 | Wayne (Joaquín en español) | +86-13316959821 | wayne@shumatt.com |
| 12 | Sylvia | +86-18312499884 | sales6@shumatt.com |

Visit <http://shumatt.com> to obtain the latest information of salesmen

PS: Shumatt's salesmen's emails are all end with @shumatt.com

6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "**17x7x1MM Injector Nozzle Copper Washer Shim Technical File**" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "**17x7x1MM Injector Nozzle Copper Washer Shim Technical File**" in any way. At the same time, any conditions to spread, repost, display the contents of "**17x7x1MM Injector Nozzle Copper Washer Shim Technical File**" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "**17x7x1MM Injector Nozzle Copper Washer Shim Technical File**" will violate the "*Copyright Law of the People's Republic of China*" and other laws and regulations and the provisions of relevant international conventions.